VISION

Orange Plus 623 i

i – injection



UNIQUE BENEFITS



Vision Perfect Cooking

Make your diners great reason to keep returning to your place. With Retigo Vision combi ovens, you have the peace of mind that you will always achieve outstanding cooking results. The prepared foods have a perfect colour, are juicy, crispy and healthy with a minimal fat contain.



Vision Design

Simply keeps you cooking with ease and comfort. Experience an excellent combination of features, exceptional ergonomics and attractive appearance. All this with a focus on safety, hygiene and long time reliability.



Vision Controls

Gives you time to concentrate on cooking and things that really matter to you. The simpliest controls quickly and easily make all the necessary settings. Panel response is perfect even with grease or gloved



Smart Investment

Generates money on savings for you every day. consumption automatic cleaning will ensure you great return on investment.

























FEATURES & BENEFITS

Cooking

- Hot air 30 300 °C
- Combination 30 300 °C
- Steaming 30 130 °C
- Bio steaming 30 98 °C
- Over night cooking Saves time and money.
- Advanced steam generation system Two-step water preheating with in-built heat exchanger for perfect steam cooking results.
- Crosswise racks Safer and comfortable GN handling. Better product visual control.
- Regeneration/banqueting Cook, chill and regenerate to serve more diners in shorther times.
- Low temperature cooking Benefit from less weight loss, better taste.
- Automatic preheating/cooling minimises the loading temperature drop. Start cooking with the desired temperature.
- Sous-vide, Drying, Sterilization, Confit, Smoking Great way to make your menu special.

Vision Controls

- 7" display Perfect overview, easy and intuitive control.
- 99 programs with 9 steps
- Continuous cooking time option Saves your time during busy operations.
- Automatic start The ability to schedule a delayed start.

Other equipment

- Active Cleaning Low-cost automatic cleaning. No chef's time spent on cleaning any more.
- Double glazed door glass Advanced energy savings and external glass that does not burn you.
- Auto-reversing fan Excellent evenness to deliver high product color and texture uniformity.
- Massive door handle Comfortable and safe handling with silver ion material contain for bacteria reduction.
- AISI 304 stainless steel Exceptional quality with a special coating for a extended life time.
- Hygienic cooking chamber with round inner corners Trouble free maintenance
- Run-off tray under the door No slipping on wet floor.
- Two water inlets Saves a water treatment unit's capacity.
- WSS (Water Saving System) Special drain system & in-built heat exchanger to save water related cost.
- Removable GN holders with 65 mm spacing

Conectivity

- USB plug-in Transfer useful data easily to and from the combi oven.
- Ethernet/LAN Allows remote access for data management.
- VisionCombi software Program and pictogram management in your PC, HACCP data view.

Operation logs

- HACCP records Easy and immediate analysis of critical cooking points.
- Complete operating records

Service

 SDS (Service Diagnostic System) – Easy unit check up and trouble shooting.

Unit options

- Left door
- · Safety door opening in two steps
- One point core probe
- Flap valve
- Standard hand shower
- · Connection to the system for power consumption optimalization

Optional accessories

ST 623 stand with capacity $16 \times GN 1/1$ ST 623 CS STAND ST 623 on wheels

KN 623 console for wall installation

VISION VENT condensation hood

OIL SPRAY GUN

VISION SMOKER

ACCESSORIES – Gastro containers, cleaning agents, water treatments

TECHNICAL DATA

Model	O 623 i+
Technical specification	2E0623IZ
Heat source	Electricity
Steam generator	Injection
Capacity	6 x GN 2/3
Capacity of meals	30 – 50
Spacing	65 mm
Dimensions (w x h x d)	683 x 602 x 586 mm
Weight	62 kg
Total power	5 (3,4*) kW
Heat power	4,8 (3,2*) kW
Fuse	16 A
Voltage	3N~/380-415V/50-60 Hz
Noise level	max. 70 dBA
Water/Drain connection	G 3/4" / 40 mm
Temperature	30 − 300 °C

^{*} Valid for voltage 1N~(2~)/220-240V/50-60 Hz

STACKING OPTIONS

Lower unit	Upper unit
623	623

OPTIONAL VOLTAGE

1N~(2~)/220-240V/50-60 Hz	
3~/200-208V/50-60Hz	
3~/220-240V/50-60Hz	
3~/400V/50-60Hz	
3~/440-480V/50-60Hz	

MARINE VERSION**

3~/400V/50-60Hz 3~/440-480V/50-60Hz

** Marine Version includes: special voltage specification, door piston for slow door open, special tray holders with barrier against slipping of GN. Available for units equipped with advanced direct system only.

DRAWINGS

